

A25-4

Type Size: S1

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Quick connect

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage U_i						
		Voltage (V)		AC / DC		
		690		AC / DC		
Rated impulse withstand voltage U_{imp}						
Voltage (kV)	Overvoltage category	Pollution degree	Supply system		Function	
6	III	3	Valid for lines with grounded common neutral termination		Switch	
Rated uninterrupted current I_u/I_{th}						
Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements			
25	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C			
Conventional enclosed thermal current I_{the}						
Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
25	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--
Rated operational current I_e						
Utilization category			Voltage (V)	Current (A)		
AC-15			220 - 240	8		
AC-15			380 - 440	5		
AC-20A			690	25		
AC-21A			24 - 48	25		
AC-21A			110 - 220	25		
AC-21A			380 - 440	25		
AC-21A			500 - 600	25		
AC-21A			660 - 690	25		
AC-22A			220 - 500	25		
AC-22A			660 - 690	25		
Rated operational power						
Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)		
AC-2	220 - 240	3	3	5,50		
AC-2	380 - 440	3	3	11		
AC-2	500	3	3	15		
AC-2	660 - 690	3	3	13		
AC-3	220 - 240	3	3	4		
AC-3	380 - 440	3	3	7,50		
AC-3	500	3	3	7,50		
AC-3	660 - 690	3	3	7,50		
AC-3	110	1	2	1,50		
AC-3	220 - 240	1	2	3		
AC-3	380 - 440	1	2	3,70		
AC-4	220 - 240	3	3	1		
AC-4	380 - 440	3	3	2,20		
AC-4	500	3	3	2,50		
AC-4	660 - 690	3	3	2,50		
AC-4	110	1	2	0,20		
AC-4	220 - 240	1	2	0,50		
AC-4	380 - 440	1	2	0,80		
AC-23A	220 - 240	3	3	5,50		
AC-23A	380 - 440	3	3	11		
AC-23A	380 - 440	3	3	11		
AC-23A	500	3	3	11		

Rated operational power				
Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-23A	660 - 690	3	3	11
AC-23A	110	1	2	1,50
AC-23A	220 - 240	1	2	3
AC-23A	380 - 440	1	2	5,50

Max. Fuse rating IEC			
Fuse characteristic	No. of Fuses	Current (A)	
gG	1	35	

UL60947-4-1 , UL508

Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
25	0 - 40	-	

GENERAL TECHNICAL INFORMATION

Rated short-time withstand current Icw		
Time (s)	Current (A)	
1	220	

Approbations	
Specification	Marking

CE marking 

UK Directives
IEC 60947-3; EN 60947-3; VDE 0660 Teil107 

UL 60947-4-1; CSA C22.2 No. 60947-4-1 

Power loss per pole	
Power (W)	
0,70	

Conditions during transport and storing			
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements	
-40	85	In case of temperatures below -5°C no shock load permissible	

General Information

- Text**
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
 - After wiring, ALL terminal screws must be tightened to the specified torque values.
 - The protection class of the selected mounting type may vary if optional extras are used.
 - Do not lubricate or treat contacts.
 - Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
 - Use only fully insulated cable lugs resp. FASTON receptacles.
 - After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

Operating temperature		
Min. Temperature [°C]	Max. Temperature [°C]	
-25	60	