



Sample image

C26X

Type Size: S1

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage U_i

Voltage (V)	AC / DC
690	AC

Rated impulse withstand voltage U_{imp}

Voltage (kV)	Overvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnecter

Rated uninterrupted current I_u/I_{th}

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
32	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C

Rated operational current I_e

Utilization category	Voltage (V)	Current (A)
AC-15	220 - 240	14
AC-15	380 - 440	6
AC-20A	690	32
AC-21A	20 - 690	32
AC-22A	220 - 500	32
AC-22A	660 - 690	32

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-2	220 - 240	3	3	8
AC-2	380 - 440	3	3	15
AC-2	500 - 500	3	3	18,50
AC-2	660 - 690	3	3	15
AC-3	220 - 240	3	3	5,50
AC-3	380 - 440	3	3	11
AC-3	500 - 500	3	3	11
AC-3	660 - 690	3	3	11
AC-3	110 - 120	1	2	2,20
AC-3	220 - 240	1	2	4
AC-3	380 - 440	1	2	5,50
AC-4	220 - 240	3	3	2,70
AC-4	380 - 440	3	3	5,50
AC-4	500 - 500	3	3	5,50
AC-4	660 - 690	3	3	5,50
AC-4	110 - 120	1	2	0,75
AC-4	220 - 240	1	2	1,50
AC-4	380 - 440	1	2	3
AC-23A	220 - 240	3	3	7,50
AC-23A	380 - 440	3	3	15
AC-23A	500 - 500	3	3	15
AC-23A	660 - 690	3	3	15
AC-23A	110 - 120	1	2	2,20
AC-23A	220 - 240	1	2	4

Rated operational power				
Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-23A	380 - 440	1	2	7,50
Max. Fuse rating IEC				
Fuse characteristic	No. of Fuses			Current (A)
gG	1			50

UL60947-4-1, UL508

Rated insulation voltage Ui			
Voltage (V)		AC / DC	
600		AC	
Rated thermal current			
Current (A)	Ambient temperature (°C)		Additional Text
40	0 - 40		--

CSA

Rated insulation voltage Ui			
Voltage (V)		AC / DC	
600		AC	
Rated thermal current			
Current (A)	Ambient temperature (°C)		Additional Text
40	0 - 40		--

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
tightening torque (Nm)		tightening torque (lb-in)
1,30		12

Rated short-time withstand current Icw		
Time (s)		Current (A)
1		350

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm ²) or (AWG/kcmil)	Material of the wire
Flexible wire	Max.	2	6mm ²	Copper
Flexible wire	Max.	2	AWG 10	Copper
Single-core or stranded wire	Max.	2	6mm ²	Copper
Single-core or stranded wire	Max.	2	AWG 8	Copper
Flexible wire with ferrule according to DIN 46228	Max.	2	4mm ²	Copper

Approbations		Marking
Specification		
CE marking		
UK Directives		
IEC 60947-3; EN 60947-3; VDE 0660 Teil107		IEC 60947-3 EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1		
---------------------------------------	--	---

Power loss per pole	
Power (W)	
1,30	

Conditions during transport and storing			
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements	
-40	85	In case of temperatures below -5°C no shock load permissible	

General Information	
Text	

- Use only copper wires with or without tinned/silver-plated individual wires. Soldering the end of the wire before wiring is not allowed.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- The coil of the under-voltage release contains voltage-sensitive components. To avoid destruction of these components the coil shall be disconnected during voltage testing.

General Information*Text*

- Use only fully insulated cable lugs resp. FASTON receptacles.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.
- Appliances have no trip free release!

Operating temperature*Min. Temperature [°C]*

-5

Max. Temperature [°C]

40