



Sample image

C317

Type Size: S3

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Bolt terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui

Voltage (V)	AC / DC
690	AC

Rated impulse withstand voltage Uimp

Voltage (kV)	Overvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnecter

Rated uninterrupted current Iu/Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
315	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C

Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-20A	690	315
AC-21A	20 - 690	315
AC-22A	220 - 500	315
AC-22A	660 - 690	125

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-2	220 - 240	3	3	55
AC-2	380 - 440	3	3	90
AC-2	500 - 500	3	3	110
AC-2	660 - 690	3	3	55
AC-3	220 - 240	3	3	37
AC-3	380 - 440	3	3	55
AC-3	500 - 500	3	3	55
AC-3	660 - 690	3	3	37
AC-3	110 - 120	1	2	11
AC-3	220 - 240	1	2	22
AC-3	380 - 440	1	2	30
AC-4	220 - 240	3	3	15
AC-4	380 - 440	3	3	25
AC-4	500 - 500	3	3	25
AC-4	660 - 690	3	3	22
AC-4	110 - 120	1	2	4
AC-4	220 - 240	1	2	7,50
AC-4	380 - 440	1	2	11
AC-23A	220 - 240	3	3	75
AC-23A	500 - 500	3	3	132
AC-23A	660 - 690	3	3	37
AC-23A	380 - 440	3	3	132
AC-23A	110 - 120	1	2	18,50
AC-23A	220 - 240	1	2	37
AC-23A	380 - 440	1	2	55

Max. Fuse rating IEC

Fuse characteristic	No. of Fuses	Current (A)
gG	1	315

UL60947-4-1 , UL508

Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	260	0 - 40	--

General Information	
Text	
- For field wiring use the following Listed cable lugs type YA29LBOX manufactured by Burndy or CRA-250L or CRA-250 manufactured by IlSCO or BLU-025S manufactured by Penn-Union.	

CSA			
Rated insulation voltage Ui			
	Voltage (V)	AC / DC	
	600	AC	

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	240	0 - 40	--

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
	tightening torque (Nm)	tightening torque (lb-in)
	14	125

Rated short-time withstand current Icw		
	Time (s)	Current (A)
	1	4200

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm ²) or (AWG/kcmil)	Material of the wire
Flexible wire	Max.	1	MCM 300	Copper
Flexible wire	Max.	1	150mm ²	Copper
Single-core or stranded wire	Max.	1	185mm ²	Copper
Single-core or stranded wire	Max.	1	MCM 350	Copper

Approbations	
Specification	Marking

CE marking	
------------	---------------------------------------------------------------------------------------

UK Directives	
IEC 60947-3; EN 60947-3; VDE 0660 Teil107	IEC 60947-3 EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1	
---------------------------------------	---------------------------------------------------------------------------------------

CSA C.22.2 No.14	
------------------	---------------------------------------------------------------------------------------

Power loss per pole	
	Power (W)
	17

Conditions during transport and storing			
	Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
	-40	85	In case of temperatures below -5°C no shock load permissible

Shock / Vibration	
Type of oscillation	Values
Resistance to shock	min. 5g, 30ms

General Information	
Text	

- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

Operating temperature		
	Min. Temperature [°C]	Max. Temperature [°C]
	-5	60

Dimensions ring cable lug

A(mm)

28,20 mm