



Sample image

## C32C

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

### IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

#### Rated insulation voltage Ui

| Voltage (V) | AC / DC |
|-------------|---------|
| 690         | 50/60Hz |

#### Rated impulse withstand voltage Uimp

| Voltage (kV) | Oversvoltage category | Pollution degree | Supply system  | Function |
|--------------|-----------------------|------------------|--|----------|
| 6            | III                   | 3                | Valid for lines with grounded common neutral termination | Switch   |

#### Rated uninterrupted current Iu/Ith

| Current (A) | Ambient temperature (°C) | Peak temperature (°C) | additional requirements  |
|-------------|--------------------------|-----------------------|--|
| 50          | 55                       | 60                    | Ambient temperature +55°C during 24 hours with peaks up to +60°C |

#### Rated operational current Ie

| Utilization category | Voltage (V) | Current (A) |
|----------------------|-------------|-------------|
| AC-15                | 220 - 240   | 16          |
| AC-15                | 380 - 440   | 7           |
| AC-20A               | 690         | 50          |
| AC-21A               | 20 - 690    | 40          |
| AC-22A               | 220 - 500   | 40          |
| AC-22A               | 660 - 690   | 40          |

#### Rated operational power

| Utilization category | Voltage (V) | No. of phases | No. of poles | Power (kW) |
|----------------------|-------------|---------------|--------------|------------|
| AC-2                 | 220 - 240   | 3             | 3            | 10         |
| AC-2                 | 380 - 440   | 3             | 3            | 18,50      |
| AC-2                 | 500 - 500   | 3             | 3            | 22         |
| AC-2                 | 660 - 690   | 3             | 3            | 22         |
| AC-3                 | 220 - 240   | 3             | 3            | 7,50       |
| AC-3                 | 380 - 440   | 3             | 3            | 15         |
| AC-3                 | 500 - 500   | 3             | 3            | 15         |
| AC-3                 | 660 - 690   | 3             | 3            | 15         |
| AC-3                 | 110 - 120   | 1             | 2            | 2,50       |
| AC-3                 | 220 - 240   | 1             | 2            | 5,50       |
| AC-3                 | 380 - 440   | 1             | 2            | 7,50       |
| AC-4                 | 220 - 240   | 3             | 3            | 3,70       |
| AC-4                 | 380 - 440   | 3             | 3            | 6          |
| AC-4                 | 500 - 500   | 3             | 3            | 6          |
| AC-4                 | 660 - 690   | 3             | 3            | 6          |
| AC-4                 | 110 - 120   | 1             | 2            | 1,10       |
| AC-4                 | 220 - 240   | 1             | 2            | 2,20       |
| AC-4                 | 380 - 440   | 1             | 2            | 3,70       |
| AC-23A               | 220 - 240   | 3             | 3            | 11         |
| AC-23A               | 380 - 440   | 3             | 3            | 22         |
| AC-23A               | 500 - 500   | 3             | 3            | 30         |
| AC-23A               | 660 - 690   | 3             | 3            | 22         |
| AC-23A               | 110 - 120   | 1             | 2            | 2,50       |
| AC-23A               | 220 - 240   | 1             | 2            | 5,50       |
| AC-23A               | 380 - 440   | 1             | 2            | 11         |

#### Max. Fuse rating IEC

| Fuse characteristic | No. of Fuses | Current (A) |
|---------------------|--------------|-------------|
| gG                  | 1            | 63          |

### UL60947-4-1, UL508

#### Rated insulation voltage Ui

| Voltage (V) | AC / DC |
|-------------|---------|
|-------------|---------|

600 AC

| Rated thermal current |                          |                 |  |
|-----------------------|--------------------------|-----------------|--|
| Current (A)           | Ambient temperature (°C) | Additional Text |  |
| 50                    | 0 - 40                   | -               |  |

**CSA**

| Rated insulation voltage Ui |         |  |  |
|-----------------------------|---------|--|--|
| Voltage (V)                 | AC / DC |  |  |
| 600                         | AC      |  |  |

  

| Rated thermal current |                          |                 |  |
|-----------------------|--------------------------|-----------------|--|
| Current (A)           | Ambient temperature (°C) | Additional Text |  |
| 50                    | 0 - 40                   | -               |  |

**GENERAL TECHNICAL INFORMATION**

| Rated short-time withstand current Icw |             |  |
|--|-------------|--|
| Time (s)                               | Current (A) |  |
| 1                                      | 800         |  |

| Size of conductor                                 |                   |                               |   |                      |
|---|-------------------|-------------------------------|---|----------------------|
| composition of conductor                          | Min. / Max. value | No. of conductor per terminal | Cross section (mm <sup>2</sup> ) or (AWG/kcmil) | Material of the wire |
| Flexible wire                                     | Max.              | 2                             | 6mm <sup>2</sup>                                | Copper               |
| Flexible wire                                     | Max.              | 2                             | AWG 8   | Copper               |
| Single-core or stranded wire                      | Max.              | 2                             | 10mm <sup>2</sup>                               | Copper               |
| Single-core or stranded wire                      | Max.              | 2                             | AWG 8   | Copper               |
| Flexible wire with ferrule according to DIN 46228 | Max.              | 2                             | 6mm <sup>2</sup>                                | Copper               |

| Recommended screw driver               |       |
|--|-------|
| Type of screw driver                   | Value |
| Cross Screwdriver                      | PH2   |
| Slot screwdriver according to DIN 5264 | 1,2x8 |

  

| Tightening torque of screws |                        |                           |
|-----------------------------|------------------------|---------------------------|
|                             | tightening torque (Nm) | tightening torque (lb-in) |
|                             | 2,20                   | 19,50                     |

| Approbations                              |   |
|---|---|
| Specification                             | Marking   |
| EAC                                       |  |
| CE marking                                |  |
| UK Directives                             |  |
| IEC 60947-3; EN 60947-3; VDE 0660 Teil107 | <b>IEC 60947-3<br/>EN 60947-3</b>   |
| UL 60947-4-1; CSA C22.2 No. 60947-4-1     |  |
| CSA C.22.2 No.14                          |  |
| GB/T14048.3                               |  |

| Power loss per pole |           |
|---------------------|-----------|
|                     | Power (W) |
|                     | 1,30      |

| Conditions during transport and storing |                          |  |  |
|---|--------------------------|--|--|
| Minimum temperature (°C)                | Maximum temperature (°C) | additional requirements                                      |  |
| -40                                     | 85                       | In case of temperatures below -5°C no shock load permissible |  |

| Shock / Vibration       |                                      |
|-------------------------|--------------------------------------|
| Type of oscillation     | Values                               |
| Resistance to vibration | IEC 61373 (2010) Category 1, Class B |

| General Information |  |
|---------------------|--|
| Text                |  |

- Use only copper wires with or without tinned/silver-plated individual wires. Soldering the end of the wire before wiring is not allowed.

**General Information***Text*

- If cable lugs are used, then only use fully insulated cable lugs resp. FASTON receptacles.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

**Operating temperature***Min. Temperature [°C]*

-25

*Max. Temperature [°C]*

60