



Sample image

C32X

Type Size: S1

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui

Voltage (V)	AC / DC
690	AC

Rated impulse withstand voltage Uimp

Voltage (kV)	Oversvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnecter

Rated uninterrupted current Iu/Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
50	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C

Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-15	220 - 240	16
AC-15	380 - 440	7
AC-20A	690	50
AC-21A	20 - 690	40
AC-22A	220 - 500	40
AC-22A	660 - 690	40

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-2	220 - 240	3	3	10
AC-2	380 - 440	3	3	18,50
AC-2	500 - 500	3	3	22
AC-2	660 - 690	3	3	22
AC-3	220 - 240	3	3	7,50
AC-3	380 - 440	3	3	15
AC-3	500 - 500	3	3	15
AC-3	660 - 690	3	3	15
AC-3	110 - 120	1	2	2,50
AC-3	220 - 240	1	2	5,50
AC-3	380 - 440	1	2	7,50
AC-4	220 - 240	3	3	3,70
AC-4	380 - 440	3	3	6
AC-4	500 - 500	3	3	6
AC-4	660 - 690	3	3	6
AC-4	110 - 120	1	2	1,10
AC-4	220 - 240	1	2	2,20
AC-4	380 - 440	1	2	3,70
AC-23A	220 - 240	3	3	11
AC-23A	380 - 440	3	3	22
AC-23A	500 - 500	3	3	30
AC-23A	660 - 690	3	3	22
AC-23A	110 - 120	1	2	2,50
AC-23A	220 - 240	1	2	5,50
AC-23A	380 - 440	1	2	11

Max. Fuse rating IEC		
Fuse characteristic	No. of Fuses	Current (A)
gG	1	63

UL60947-4-1 , UL508

Rated insulation voltage Ui		
Voltage (V)	AC / DC	
600	AC	

Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
50	0 - 40	-	

CSA

Rated insulation voltage Ui		
Voltage (V)	AC / DC	
600	AC	

Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
50	0 - 40	-	

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
tightening torque (Nm)	tightening torque (lb-in)	
2,20	19,50	

Rated short-time withstand current Icw		
Time (s)	Current (A)	
1	800	

Size of conductor					
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm ²) or (AWG/kcmil)	Material of the wire	
Flexible wire	Max.	2	6mm ²	Copper	
Flexible wire	Max.	2	AWG 8	Copper	
Single-core or stranded wire	Max.	2	10mm ²	Copper	
Single-core or stranded wire	Max.	2	AWG 8	Copper	
Flexible wire with ferrule according to DIN 46228	Max.	2	6mm ²	Copper	

Approbations	
Specification	Marking

CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



Power loss per pole	
Power (W)	
1,30	

Conditions during transport and storing			
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements	
-40	85	In case of temperatures below -5°C no shock load permissible	

General Information	
Text	

- Use only copper wires with or without tinned/silver-plated individual wires. Soldering the end of the wire before wiring is not allowed.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- The coil of the under-voltage release contains voltage-sensitive components. To avoid destruction of these components the coil shall be disconnected during voltage testing.

General Information*Text*

- Use only fully insulated cable lugs resp. FASTON receptacles.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.
- Appliances have no trip free release!

Operating temperature*Min. Temperature [°C]*

-5

Max. Temperature [°C]

40