Kraus & Naimer

Datasheet

Sample image

CH10B-1

Type Size: S1

Classification Contact: Rigid contact bridge

Classification Contact Mat: Gold

Classification Terminal: Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui

Voltage (V)	AC / DC
690	AC

Rated impulse withstand voltage Uimp

Voltage (kV)	Overvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	Switch

Rated uninterrupted current Iu/Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
16	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C

Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-15	220 - 240	1,50
AC-15	380 - 440	1
AC-21A	12 - 690	16

Max. Fuse rating IEC

Fuse characteristic	No. of Fuses	Current (A)
gG	1	16

UL60947-4-1 , UL508

Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current

Current (A)	Ambient temperature (°C)	Additional Text
15	0 - 40	--

GENERAL TECHNICAL INFORMATION

Tightening torque of screws

tightening torque (Nm)	tightening torque (lb-in)
1	9

Rated short-time withstand current Icw

Time (s)	Current (A)
1	130

Size of conductor

composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm²) or (AWG/kcmil)	Material of the wire
Flexible wire	Max.	2	AWG 12	Copper
Flexible wire	Max.	2	2.5mm²	Copper
Single-core or stranded wire	Max.	2	AWG 10	Copper
Single-core or stranded wire	Max.	2	4mm²	Copper
Flexible wire with ferrule according to DIN 46228	Max.	2	2.5mm²	Copper

Approbations

Specification	Marking
EAC	EAC
CE marking	CE

Approbations

Specification	*Marking*
UK Directives	
IEC 60947-3; EN 60947-3; VDE 0660 Teil107	**IEC 60947-3** **EN 60947-3**
UL 60947-4-1; CSA C22.2 No. 60947-4-1	c UL us LISTED 24D8

Power loss per pole

Power (W)
1,60

Conditions during transport and storing

Minimum temperature (°C)	*Maximum temperature (°C)*	*additional requirements*
-40	85	In case of temperatures below -5°C no shock load permissible

General Information

Text

- Use only copper wires with or without tinned/silver-plated individual wires. Soldering the end of the wire before wiring is not allowed.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

Operating temperature

Min. Temperature [°C]	*Max. Temperature [°C]*
-25	60