



Sample image

## DH10B

**Type Size: S1**
**Classification Contact: Rigid contact bridge**
**Classification Contact Mat: Silver**
**Classification Terminal: Screw terminal**
**IEC 60947-3 EN 60947-3, VDE 0660 Teil 107**

Rated insulation voltage $U_i$		Voltage (V) AC / DC				
		690	AC			
Rated impulse withstand voltage $U_{imp}$						
Voltage (kV)	Overvoltage category	Pollution degree	Supply system			
6	III	3	Valid for lines with grounded common neutral termination			
Function						
Switch						
Rated uninterrupted current $I_u/I_{th}$						
Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements			
16	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C			
Conventional enclosed thermal current $I_{the}$						
Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
16	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--
Rated operational current $I_e$						
Utilization category	Voltage (V)		Current (A)			
AC-15	110 - 240		5			
AC-15	380 - 440		3			
AC-21A	20 - 690		16			
Rated operational power						
Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)		
AC-3	220 - 240	3	3	2,20		
AC-3	380 - 440	3	3	3,70		
AC-3	500 - 500	3	3	3,70		
AC-3	660 - 690	3	3	3,70		
AC-3	110 - 120	1	2	0,37		
AC-3	220 - 240	1	2	1,10		
AC-3	380 - 440	1	2	2,20		
AC-23A	220 - 240	3	3	3		
AC-23A	380 - 440	3	3	5,50		
AC-23A	500 - 500	3	3	5,50		
AC-23A	660 - 690	3	3	4		
AC-23A	110 - 120	1	2	0,55		
AC-23A	220 - 240	1	2	1,50		
AC-23A	380 - 440	1	2	2,50		
Max. Fuse rating IEC						
Fuse characteristic	No. of Fuses		Current (A)			
gG	1		16			

**UL60947-4-1 , UL508**

Rated insulation voltage $U_i$		Voltage (V) AC / DC	
		600	AC
Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
15	0 - 40	--	

**GENERAL TECHNICAL INFORMATION**

Tightening torque of screws	
tightening torque (Nm)	tightening torque (lb-in)
0,60	5

Rated short-time withstand current low	
Time (s)	Current (A)
1	120

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm <sup>2</sup> ) or (AWG/kcmil)	Material of the wire
Flexible wire	Max.	2	2.5mm <sup>2</sup>	Copper
Flexible wire	Max.	2	AWG 14	Copper
Single-core or stranded wire	Max.	2	AWG 12	Copper
Single-core or stranded wire	Max.	2	2.5mm <sup>2</sup>	Copper
Flexible wire with ferrule according to DIN 46228	Max.	2	1.5mm <sup>2</sup>	Copper

Approbations	
Specification	Marking

CE marking



UK Directives	
---------------	--

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

**IEC 60947-3**  
**EN 60947-3**

UL 60947-4-1; CSA C22.2 No. 60947-4-1



Power loss per pole	
Power (W)	

0,70

Conditions during transport and storing		
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
-40	85	In case of temperatures below -5°C no shock load permissible

Shock / Vibration	
Type of oscillation	Values
Resistance to vibration	IEC 61373 (1999) Category 1, Class B

General Information	
Text	

- Use only copper wires with or without tinned/silver-plated individual wires. Soldering the end of the wire before wiring is not allowed.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

Operating temperature		
Min. Temperature [°C]	Max. Temperature [°C]	
-25	60	