

DK11

Type Size: S0

Classification Contact: H-Bridge

Classification Contact Mat: Gold plated

Classification Terminal: Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage U_i		Voltage (V) AC / DC	
		600	AC / DC
Rated impulse withstand voltage U_{imp}		Voltage (kV)	
		4	II
Rated uninterrupted current I_u /Ith		Pollution degree	
		3	
Conventional enclosed thermal current I_{the}		Supply system	
		Valid for lines with grounded common neutral termination	
Rated operational current I_e		Function	
		Switch	
Rated uninterrupted current I_u /Ith		additional requirements	
Current (A)	Ambient temperature (°C)	Peak temperature (°C)	
6	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C
Conventional enclosed thermal current I_{the}		Additional requirements	
Current (A)	Ambient temperature (°C)	Peak temperature (°C)	No. of stages (from - to)
6	35	40	–
		Ambient temperature +35°C during 24 hours with peaks up to +40°C	
Rated operational current I_e		Mounting	
		–	
Rated operational current I_e		Mounting size	
		–	
Max. Fuse rating IEC		Voltage (V)	
Fuse characteristic		Current (A)	
gG		1	6

UL60947-4-1, UL508

Rated insulation voltage U_i		Voltage (V) AC / DC	
		600	AC
Rated thermal current		Ambient temperature (°C)	
Current (A)		0 - 40	–
6			

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		tightening torque (Nm)		tightening torque (lb-in)	
		0,60			5
Rated short-time withstand current I_{sc}		Time (s)		Current (A)	
		1			40
Size of conductor		No. of conductor per terminal		Material of the wire	
composition of conductor	Min. / Max. value		Cross section (mm ²) or (AWG/kcmil)		
Solid wire	Min.	1	0.5mm ²		Copper
Solid wire	Min.	2	0.5mm ²		Copper

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm ²) or (AWG/kcmil)	Material of the wire
Flexible wire	Min.	1	0.75mm ²	Copper
Flexible wire	Min.	2	0.75mm ²	Copper
Flexible wire	Max.	2	2.5mm ²	Copper
Flexible wire	Max.	2	AWG 14	Copper
Single-core or stranded wire	Max.	2	AWG 12	Copper
Single-core or stranded wire	Max.	2	2.5mm ²	Copper
Flexible wire with ferrule according to DIN 46228	Min.	1	0.5mm ²	Copper
Flexible wire with ferrule according to DIN 46228	Max.	2	1.5mm ²	Copper
Flexible wire with ferrule according to DIN 46228	Min.	2	0.5mm ²	Copper

Approbations	
Specification	Marking

CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1



Power loss per pole	
	Power (W)
	0,20

Conditions during transport and storing		
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
-40	85	In case of temperatures below -5°C no shock load permissible

Shock / Vibration	
Type of oscillation	Values
Resistance to vibration	IEC 61373 (1999) Category 1, Class B

General Information	
Text	

- Use only copper wires with or without tinned/silver-plated individual wires. Soldering the end of the wire before wiring is not allowed.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

Operating temperature	
Min. Temperature [°C]	Max. Temperature [°C]
-5	60