

Sample image

## KG162

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Bolt terminal/Screw terminal

### IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

#### Rated insulation voltage Ui

Voltage (V)	AC / DC
1000	AC

#### Rated impulse withstand voltage Uimp

Voltage (kV)	Overvoltage category	Pollution degree	Supply system	Function
8	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnecter

#### Rated uninterrupted current Iu/Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
160	50	55	Ambient temperature +50°C during 24 hours with peaks up to +55°C

#### Conventional enclosed thermal current Ithe

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
160	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

#### Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-32A	20 - 400	160
AC-20A	1000	160
AC-21A	20 - 690	160
AC-22A	220 - 500	160
AC-22A	660 - 690	100

#### Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-3	220 - 240	3	3	30
AC-3	380 - 440	3	3	45
AC-3	500 - 500	3	3	55
AC-3	660 - 690	3	3	37
AC-23A	220 - 240	3	3	30
AC-23A	380 - 440	3	3	55
AC-23A	500 - 500	3	3	75
AC-23A	660 - 690	3	3	37

#### Max. Fuse rating IEC

Fuse characteristic	No. of Fuses	Current (A)
gG	1	160

### UL60947-4-1 , UL508

#### Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

#### Rated thermal current

Current (A)	Ambient temperature (°C)	Additional Text
200	0 - 40	--

#### General Information




##### Text

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.

### CSA

#### Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current				
Current (A)		Ambient temperature (°C)	Additional Text	
200		0 - 40	--	
GENERAL TECHNICAL INFORMATION				
Tightening torque of screws				
		tightening torque (Nm)	tightening torque (lb-in)	
		14	125	
Rated short-time withstand current I <sub>sw</sub>				
		Time (s)	Current (A)	
		1	3000	
Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm²) or (AWG/kcmil)	Material of the wire
Flexible wire	Max.	1	70mm²	Copper
Flexible wire	Max.	1	AWG 2/0	Copper
Single-core or stranded wire	Max.	1	95mm²	Copper
Single-core or stranded wire	Max.	1	AWG 3/0	Copper
Flexible wire with sleeve	Max.	1	70mm²	Copper
Approbations				
Specification				Marking
CE marking				
UK Directives				
IEC 60947-3; EN 60947-3; VDE 0660 Teil107				IEC 60947-3 EN 60947-3
IEC 60947-6-1				IEC 60947-6-1 EN 60947-6-1
UL 60947-4-1; CSA C22.2 No. 60947-4-1				
CSA C.22.2 No.14				
Power loss per pole				
				Power (W)
				5
Conditions during transport and storing				
Minimum temperature (°C)		Maximum temperature (°C)	additional requirements	
-40		85	In case of temperatures below -5°C no shock load permissible	
General Information				
Text				
<div>- The wiring aid has to be removed before voltage is applied!</div> <div>- EMC Note: This device is suitable for use in environment A and B.</div> <div>- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.</div> <div>- After wiring, ALL terminal screws must be tightened to the specified torque values.</div> <div>- The protection class of the selected mounting type may vary if optional extras are used.</div> <div>- Do not lubricate or treat contacts.</div> <div>- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.</div>				
Operating temperature				
		Min. Temperature [°C]	Max. Temperature [°C]	
		-5	55	



Dimensions ring cable lug

A(mm)	20,00 mm
A(mm)	25,00 mm